



Main

| | |
|--------------------------------|----------------------|
| Range of product | Digilink |
| Product or component type | Patch panel |
| Provided equipment | With RJ45 connectors |
| Communication network category | 6 |
| Cable shielding type | UTP |
| Number of port | 24 |

Complementary

| | |
|-----------------------|--|
| Connector type | RJ45 |
| Number of matings | 750 cycles |
| [In] rated current | ≤ 1.5 A |
| Insulation resistance | ≥ 500 mOhm @ 500 V DC |
| Contact resistance | ≤ 20 mOhm |
| Material | Powder coated steel panel |
| Contacts material | Phosphor bronze with 50 micro-inches gold over 100 micro-inches nickel |
| Width | 482.6 mm |
| Height | 44.2 mm |
| Number of rack unit | 1U |

Environment

| | |
|------------------------------|---|
| Environmental characteristic | Flame retardant |
| Product certifications | UL listed UL/ETL verified |
| Standards | ANSI/TIA-568-C.2 ISO/IEC 11801 class E EIA/TIA TSB 40 A |

Contractual warranty

| | |
|--------|-----------|
| Period | 18 months |
|--------|-----------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.